

VOMAX[®]

PRODUCT CATALOG



SPECIFICATIONS FOR 999-HAND DRILL



POWER (W)	VOLTAGE (V)	SAFE RANGE OF HIGH PRESSURE HOSE	MAX OUTPUT PRESSURE	RESTARTED PRESSURE
910W	220V/50HZ	14000 PSI	18000 PSI	7500 PSI

**VOMAX 9999 GROUNDING MACHINE
HAND DRILL TYPE**



POWER (W)	VOLTAGE (V)	SAFE RANGE OF HIGH PRESSURE HOSE	MAX OUTPUT PRESSURE	RESTARTED PRESSURE
910W	220V/50HZ	14000 PSI	18000 PSI	7500 PSI

VOMAX 9999 GROUNDING MACHINE

**GROUNDING PUMP
PAINT SPRAYER
AIR SANDER
POKER**



POWER (W)	VOLTAGE (V)	MAX OUTPUT PRESSURE	SECOND START PRESSURE	MAX EXPLOSION PRESSURE
1100W	220V/50HZ	15000 PSI	8500 PSI	18000 PSI

9999-2 TWO COMPONENT GROUNDING MACHINE



MAX. SPEED	WORKING PRESSURE	HOSE SIZE	AIR INLET SIZE	SANDPAPER SIZE
10000 RP	90PSI	3/8"	1/4"	125MM

TOP-213 5" AIR SANDER



SPECIFICATIONS FOR POKER

POWER (W)	VOLTAGE (V)	POKER HEAD DIAMETER	RPM	MAINS CABLE (METER)
1200	220V-50HZ	35	4200	1.2/1.5

VOMAX POKER SET (1.2M/1.5M/2M)



SPECIFICATIONS FOR VMX980

MOTOR POWER (W)	MAXIMUM FLOW (L/min)	MAXIMUM PRESSURE	LONGEST TAKEOVER	VOLTAGE FREQUENCY
4000W	20 L/min	3200 PSI	15-45M	220V 50/60Hz

VOMAX 980 AIRLESS PAINT SPRAYER



SPECIFICATIONS FOR APS1400

MOTOR POWER (W)	MAXIMUM FLOW (L/min)	MAXIMUM PRESSURE	MAX.TIP SIZE	VOLTAGE FREQUENCY
3500W	22L/min	3300 PSI	0.029	220V

APS1400 AIRLESS PAINT SPRAYER



SPECIFICATIONS FOR VMX-Q909B

TANK CAPACITY	WORKING PRESSURE	MAX OPERATING PRESSURE	MATERIAL	ACCESSORIES
70 LITER	1-3BAR (14.5-43.5 PSI)	4 BAR (58 PSI)	STAINLESS STEEL	HOSE,NOZZLE

VOMAX Q909B S/STEEL SNOW WASH TANK